



Godson Ultimate Bending Solutions

An ISO 9001 : 2008 Certified Company [®]

GODSON

Hydraulic Press Brake



[®]

GODSON

Godson bending systems pvt. ltd.

ATIKA IND. AREA, MARG NO. 1, DHEBAR ROAD (SOUTH), RAJKOT-360 002 (INDIA)
Ph.: +91 - 281 - 2361467, 2361449 * Fax: +91-281-2361873
Website: www.godson-india.com | E-mail: godsonindia@hotmail.com



CRISIL
RATINGS



HYDRAULIC PRESS BRAKE

MODEL	TONAGE	BENDING CAP M.M. (M.S)	TABLE WIDTH	CLEAR DISTANCE	RAM STROKE	OPEN HEIGHT	DEPTH	POWER H.P.	SPEED APPRX.REI.	PACKING DIMENSIONM.M. (LXWXH)
GPBR - 1	20	1270X2.5	125	900	100	250	200	3	35-9-60	1400x1050x1900
GPBR - 2	20	1525X2	125	1100	100	250	200	3	35-9-60	1700x1050x1900
GPBR - 3	30	1270X3	125	900	100	250	200	3	30-9-53	1400x1050x1900
GPBR - 4	30	1525X2.15	125	1100	100	250	200	3	30-9-53	2700x1050x1900
GPBR - 5	30	2030X2	125	1500	100	250	200	3	30-9-53	2200x1050x1900
GPBR - 6	30	2540X1.6	125	2000	100	250	200	3	30-9-53	2700x1050x1900
GPBR - 7	40	1270X4	150	900	100	250	200	5	35-9-55	1400x1050x1900
GPBR - 8	40	1525X3	150	1100	100	250	200	5	35-9-55	1700x1050x1900
GPBR - 9	40	2030X2.5	150	1550	100	250	200	5	35-9-55	2200x1050x1900
GPBR - 10	40	2540X2	150	2000	100	250	200	5	35-9-55	2700x1050x1900
GPBR - 11	40	3125X1.6	150	2500	400	250	200	5	35-9-55	3300x1050x1900
GPBR - 12	50	1270X5	175	900	125	250	200	5	30-7-55	1400x1050x1900
GPBR - 13	50	1525X4	175	1100	125	250	200	5	30-7-55	1700x1050x1900
GPBR - 14	50	2030X3	175	1550	125	250	200	5	30-9-55	2200x1050x1900
GPBR - 15	50	2540X2.5	175	2000	125	250	200	5	30-7-55	2700x1050x1900
GPBR - 16	50	3125X2	175	2500	125	250	200	5	30-7-55	3300x1050x1900
GPBR - 17	60	1270X6	175	900	125	250	200	5	25-6-50	1400x1200x2000
GPBR - 18	60	1525X5	175	1100	125	330	200	5	25-6-50	1700x1200x2000
GPBR - 19	60	2030X4	175	1550	125	330	200	5	25-6-50	2200x1200x2000
GPBR - 20	60	2540X3	175	2000	125	330	200	5	25-6-50	2700x1200x2000
GPBR - 21	60	3125X2.5	175	2500	125	330	200	7.5	25-6-50	3300x1200x2000
GPBR - 22	80	1270X8	200	400	150	330	200	7.5	37-6-41	1400x1500x2200
GPBR - 23	80	1525X6	200	1100	150	330	250	7.5	37-6-41	1700x1500x2200
GPBR - 24	80	2030X5	200	1550	150	330	250	7.5	37-6-41	2200x1500x2200
GPBR - 25	80	2540X4	200	2000	150	330	250	7.5	37-6-41	2700x1500x2200
GPBR - 26	80	3125X3	200	2500	150	330	250	7.5	37-6-41	3300x1500x2200
GPBR - 27	80	4000X2.5	200	3500	150	330	250	7.5	37-6-41	4200x1500x2200
GPBR - 28	100	1270X10	200	900	150	330	250	7.5	40-5-40	1400x1500x2300
GPBR - 29	100	1525X8	200	1100	150	330	250	7.5	40-5-40	1700x1500x2300
GPBR - 30	100	2030X6	200	1550	150	330	250	7.5	40-5-40	2200x1600x2300
GPBR - 31	100	2540X5	200	2000	150	330	250	7.5	40-5-40	2700x1600x2300
GPBR - 32	100	3125X4	200	2500	150	330	250	7.5	40-5-40	3300x1600x2300
GPBR - 33	100	4000X3	200	3000	150	330	250	7.5	40-5-40	4200x1600x2300
GPBR - 34	100	5000X2.5	200	4000	150	330	250	7.5	40-5-40	5200x1600x2300
GPBR - 35	100	6000X2	200	5000	150	330	250	7.5	40-5-40	6200x1600x2300
GPBR - 36	120	1270X12	125	900	150	330	300	10	41-6-41	1400x1700x2300
GPBR - 37	120	1525X10	125	1100	150	330	300	10	41-6-41	1700x1700x2500
GPBR - 38	120	2030X8	125	1550	150	330	300	10	41-6-41	2200x1700x2800
GPBR - 39	120	2540X6	125	2000	150	330	300	10	41-6-41	2700x1700x2500
GPBR - 40	120	3125X5	125	2500	150	330	300	10	41-6-41	3300x1700x2500
GPBR - 41	120	4000X4	125	3000	150	330	300	10	41-6-41	4200x1700x2500
GPBR - 42	120	5000X3	125	4000	150	330	300	10	41-6-41	5200x1700x2500
GPBR - 43	120	6000X2.5	125	5000	150	330	300	10	41-6-41	6200x1700x2500
GPBR - 44	160	1270X16	125	900	200	375	300	15	40-6-40	1400x1800x2500
GPBR - 45	160	1525X12	125	1100	200	375	300	15	40-6-40	1700x1800x2500
GPBR - 46	160	2030X10	125	1550	200	375	300	15	40-6-40	2200x1800x2500
GPBR - 47	160	2540X8	125	2000	200	375	300	15	40-6-40	2700x1800x2500
GPBR - 48	160	3125X6	125	2500	200	375	300	15	40-6-40	3300x1800x2500
GPBR - 49	160	4000X5	125	3000	200	375	300	15	40-6-40	4200x1800x2500
GPBR - 50	160	5000X4	125	4000	200	375	300	15	40-6-40	5200x1800x2500
GPBR - 51	150	6000X3	225	5000	200	375	300	15	40-6-40	6200X1800X2500
GPBR - 52	200	2030X12	250	1550	200	375	300	20	37-5-37	2200X2000X2600
GPBR - 53	200	2540X10	250	2000	200	375	300	20	37-5-37	2700X2000X2600
GPBR - 54	200	3125X8	250	2500	200	375	300	20	37-5-37	3300X2000X2600
GPBR - 55	200	4000X6	250	3000	200	375	300	20	37-5-37	4200X2000X2600
GPBR - 56	200	5000X5	250	4000	200	375	300	20	37-5-37	5200X2000X2600
GPBR - 57	200	6000X4	250	5000	200	375	300	20	37-5-37	6200X2000X2600
GPBR - 58	250	2030X16	250	1550	200	375	300	25	40-5-40	2200X2100X2700
GPBR - 59	250	2540X13	250	2000	200	375	300	25	40-5-40	2700X2100X2700
GPBR - 60	250	3125X10	250	2500	200	375	300	25	40-5-40	3300X2100X2700
GPBR - 61	250	4000X8	250	3000	200	375	300	25	40-5-40	4200X2100X2700
GPBR - 62	250	5000X6	250	4000	200	375	300	25	40-5-40	5200X2100X2700
GPBR - 63	250	6000X5	250	5000	200	375	300	25	40-5-40	6200X2100X2700

Capacities rated for M.s. Of U.T.S. 45kg/mm2 & S.S. Of U.T.S. 72kg./,2 Machine will not cut any thickness variation beyond rated capacity for any length. Right to change specification, features, features, accessories without notice reserved. Compliance with safety requirements as per local regulations is responsibility of the user.